



- Zero transfer time to protect mission-critical loads such as servers and ATM.
- Removable LCD control module with multiple communications
- Built-in Bluetooth for mobile monitoring (Android App is available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Built-in anti-dusk filters
- Configurable AC/PV output usage timer and prioritization
- Optional parallel operation up to 9 units

MODEL	Apert King 3K	Apert King 5K
Rated Power	3000VA/3000W	5000VA/5000W
Parallel Capability	Up to 9 units	Up to 9 units
INPUT		
Voltage	230 VAC	
Voltage Range	176- 280 VAC at 100% load/ 110- 280 VAC at 50% load	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation	230 VAC ± 5%	
Output THDv	<3% for linear load, <5% for non- linear load	
Surge Power	6000VA for 5 sec	10000VA for 5 sec
Efficiency (Peak)	94.4 % at Line Mode, 90% at Battery Mode	
Transfer Time	0 ms	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC
Overcharge Protection	34 VDC	66 VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	MPPT
Maximum PV Array Open Circuit Voltage	145 VDC	
Maximum PV Array Power	1500 W	4000 W
MPP Range @ Operating Voltage	30 ~115 VDC	60-115VDC
Maximum Solar Charge Current	60 A	80 A
Maximum AC Charge Current	60 A	60 A
Maximum Charge Current	120 A	140 A
PHYSICAL		
Dimension, D x W x H (mm)	140 x 300 x 512	
Net Weight (Kgs)	11.5	12.2
Communication Interface	USB/RS232/RS485/Bluetooth/Dry- contact	
ENVIRONMENT		
Humidity	5% to 95% Relative Humidity (Non- condensing)	
Operating Temperature	0°C to 55°C	
Storage Temperature	- 15°C to 60°C	